

An ISO 9001 : 2015 Certified Company

Temporary Horizontal Rope Anchorage Line Ref: SF-HL-5001(2) & SF-HL-5001(4)

VIRAJ offers a Horizon 2 Man Temporary Horizontal Lifeline extremely easy to carry and install. It provides a suitable and safe anchorage horizontally along the entire length. Suitable for upto 2 & 4 personnel

DESIGN

- Horizontal lifeline has 2 steel O-Ring and 4 steel O-Ring to enable the user to easily attach the lanyard of his Harness to the lifeline using a connector.
- Swivel connector-specially design to prevent any twisting of the rope
- Concrete anchor strap made up of 44 mm wide polyester webbing stitched with 70mm webbing on the black for extra protection

WEBBING/ROPE

Webbing Material: Polyester
Webbing Width: 44mm. \pm 1mm.
Webbing Breaking Strength: 25 KN.
Rope Material: Polyamide
Dia: 16mm. \pm 1mm.
Rope Breaking Strength: 25 KN.

STITCHING THREAD

High-tenacity Polyester

METAL COMPONENT

Material: Alloy Steel
Finish: Silver or Golden Yellow Galvanized

CAPACITY RANGE

25 kN

RELEVANT STANDARDS

Meets or Exceeds EN 795:2012, CEN/TS 16415:2013

